



MP1850-MP2000E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 50Hz

380-415V	KVA	KW
Prime	1850.0	1480.0
Standby	2000.0	1600.0

@ 0.8 p.f.

Generator Output Rating at - 60Hz

480V	KVA	KW
Prime	N/A	N/A
Standby	N/A	N/A

@ 0.8 p.f.

Engine Data

Engine Manufacturer:	Perkins UK
Engine Model:	4016-61TRG1
Number of Cylinders:	16
Cylinder Arrangement:	60° Vee
Cycle:	4 Stroke
Bore/Stroke mm (in):	160.0 (6.3) / 190.0 (7.5)
Induction:	Turbo charged
Compression ratio:	13:1
Displacement l (cu.in):	61.12 L

General Data

	Liter	US/Gal
Fuel Tank Capacity:	N/A	N/A
Fuel Tank:	N/A	
Base Frame:	Heavy Duty-Powder Coated	
Control Panel:	Deep Sea Electronics	
Circuit Breaker:	ABB 3 Pole ACB	

*Breaker supplied loose in a standalone cabinet on open type generating sets

Performance

	50Hz		60Hz	
Engine Speed:	1500		1800	
Gross Engine Power:	<i>kWm</i>	<i>Bhp</i>	<i>kWm</i>	<i>Bhp</i>
Prime:	1648	2210	N/A	N/A
Standby:	1774	2379	N/A	N/A
Fuel Consumption:	<i>L/Hr</i>	<i>US Gal/Hr</i>	<i>L/Hr</i>	<i>US Gal/Hr</i>
Prime:	371	98	N/A	N/A
Standby:	401	106	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Length		Width		Height		Dry		Wet	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5623	221.3	2225	87.6	3549	139.7			13500	29762

* With Lube Oil

* With Lube Oil & Coolant

Rating Definition

P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

S Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. *No overload is permitted on these ratings. The alternator model is peak continuous rated (as defined in ISO 8528-3)*

Air Flow 50 Hz 60 Hz

	M ³ /min	Ft ³ /min	M ³ /min	Ft ³ /min
Combustion Air Flow:	165	5827	N/A	N/A
Exhaust Gas Flow:	400	14126	N/A	N/A
Radiator Cooling Air Flow:	2160	78399	N/A	N/A

*Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 52.3S5
Number of Bearings:	Single (1)
Insulation Class:	H
Total Harmonic Content:	<4.00%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP
Winding Pitch Code:	2/3 - (n°6S)

Principles



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

Diesel Power



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Cooling & Lubrication 50 Hz 60 Hz

	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	385	55.5	N/A	N/A
Lube Oil Capacity:	213	56.3	N/A	N/A

	°C	°F	°C	°F
Exhaust Temperature:	425	752	N/A	N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:

EN-GEN
DIESEL PRODUCTS

+44 (0)1493 738397

sales@engen-diesel.com

www.engen-diesel.com